BELKIN

USB 2.0

Hi-Speed USB 2.0 TetraHub™

Featuring **Tetra™ T4** Turbo Transaction Translator Technology

Connect your USB 2.0 and 1.1 devices

What is TetraHub T4 Technology? TetraHub T4 (Turbo Transaction Translator Technology) provides you with the best of USB 2.0 and 1.1 technology in one solution!

What is the difference between the standard USB 2.0 hub and the Belkin Hi-Speed 2.0 TetraHub? The TetraHub provides 480Mbps for all your Hi-Speed USB 2.0 devices such as Hi-Speed USB 2.0 scanners and hard drives.

Unlike other USB 2.0 hubs, the TetraHub also supplies a guaranteed 12Mbps to each port so you can connect full-speed USB 1.1 products, like USB speakers and USB video-capture devices that require full bandwidth to operate. Traditional hubs share 12Mbps bandwidth among all the ports.

Benefits

- Guarantees 12Mbps bandwidth to each port for USB 1.1 devices
- Identifies the speed of connected devices with advanced speed indicators
- Works with all your USB 2.0 and 1.1 devices
- Transfers data at up to 480Mbps for USB 2.0 devices
- Saves space on your desktop with stackable design
- Connects most devices without requiring an external power supply
- Includes a top-quality, Belkin Hi-Speed USB 2.0 Device Cable
- Supports Plug-and-Play specifications
- Allows "hot swapping" of USB devices
- Protects your equipment with over-current detection
- Comes with an industry-best, Belkin Lifetime Warranty

System Requirements: Available Hi-Speed USB 2.0 port; Windows® 98 SE, Me, 2000, and XP; Mac OS® X v10.3 or higher

Specifications:

- Compatible with USB 2.0 and 1.1 devices
- 480Mbps for Hi-Speed USB 2.0 devices
- Guaranteed12Mbps of bandwidth for each USB 1.1 device
- Compliant with Universal Serial Bus specification 2.0 (data rate 1.5/12/480Mbps)
- Backward-compatible with Universal Serial Bus specification 1.1 (data rate 1.5/12Mbps)
- Advanced Quad TT architecture for low- and full-speed devices
- Approved by USB Implementers Forum (USB-IF)

• Upstream Ports	1
• Downstream Ports	4
• Per-Port Voltage	DC +5V
• Per-Port Current	500mA (max) (self-powered mode)
• Power Mode	Self-Powered/bus-powered
• Operating Temperature	5° C ~ 40° C
• Storage Temperature	-20° C ~ 60° C
• Power Supply	Output: DC 6V 2.1A Plug Size: 5mm (outer) 2mm (center) Plug Polarity: Center Positive

Part Number	Description	UPC
F5U231	Hi-Speed USB 2.0 TetraHub	7-22868-48399-2

HI-SPEED CERTIFIED USB

Mac

WINDOWS 98 SE/2000/Me/XP COMPATIBLE

BELKIN

belkin.com

Belkin Corporation
310.898.1100
Compton • CA • USA

Belkin Components, Ltd.
+44 (0) 1933 35 2000
Rushden • United Kingdom

Belkin, Ltd.
+61 (0) 2 4372 8600
West Gosford • Australia

© 2003 Belkin Corporation. All rights reserved. All trade names are registered trademarks of respective manufacturers listed. The Mac logo and Mac OS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

23PB225